

CLAIMS

1. A method of repairing a dry-erase surface comprising:
providing a sheet comprising two sides, a first side comprising a dry-erase material
5 and a second side comprising an adhesive; and
adhering the sheet to the dry-erase surface.
2. The method of claim 1 wherein the sheet comprises paper.
- 10 3. The method of claim 1 wherein the sheet is opaque.
4. The method of claim 1 wherein the dry-erase board is discolored.
5. The method of claim 1 wherein the sheet comprises a color.
- 15 6. The method of claim 1 wherein the dry-erase surface comprises a white board.
7. The method of claim 1 wherein the second side is in contact with a removable
backing.
- 20 8. The method of claim 7 wherein the removable backing comprises silicone.
9. A method of transforming a writing surface into a dry-erase surface comprising:
providing a sheet having at least two sides, a first side comprising a dry-erase surface
25 having a surface tension greater than 30 dynes/cm and a second side comprising an adhesive;
and
adhering the sheet to the writing surface.
10. The method of claim 9 comprising writing on the dry-erase surface.
- 30 11. The method of claim 10 comprising erasing the dry-erase surface.

12. The method of claim 9 wherein the writing surface comprises a chalkboard.
13. The method of claim 9 wherein the writing surface comprises paper.
- 5 14. The method of claim 9 wherein the adhesive is removable, repositionable or permanent.
15. The method of claim 14 wherein the adhesive is removable or repositionable.
- 10 16. The method of claim 9 wherein the sheet is tinted or colored.
17. A dry-erase surface comprising:
a substrate; and
15 a heat cured resin disposed on the substrate to form the dry-erase surface wherein the dry-erase surface exhibits a surface tension of greater than 30 dynes/cm.
18. The surface of claim 17 wherein the resin comprises a polymer selected from alkyds, polyesters and acrylics.
- 20 19. The surface of claim 17 wherein the surface tension is greater than about 30 dynes/cm.
20. The surface of claim 17 comprising:
- 25 21. A dry-erase surface comprising:
a substrate; and
a heat cured resin disposed on a portion of the substrate to form the dry-erase surface wherein the surface exhibits a 60° gloss of less than about 90 gloss units.
- 30

22. The surface of claim 21 wherein the 60° gloss is less than about 70 gloss units.
23. The surface of claim 21 wherein the 60° gloss is less than about 60 gloss units.
- 5 24. The surface of claim 21 wherein the surface exhibits a surface tension of greater than 30 dynes/cm.
25. The surface of claim 21 wherein the resin comprises a polymer selected from alkyds, polyesters and acrylics.
- 10 26. An article comprising:
a plurality of sheets stacked substantially overlapped with one another;
each of at least two of the sheets comprising a first surface and a second surface,
wherein the first surface comprises a dry-erase surface and the second surface comprises a
15 removable adhesive; and
wherein the second surface of a first sheet is in contact with the first surface of a second sheet.
27. The article of claim 26 wherein the first surface of at least one of the plurality of
20 sheets exhibits a 60° gloss of less than 90 gloss units.
28. The article of claim 26 wherein the first surface exhibits a surface tension of at least 30 dynes/cm.
- 25 29. The article of claim 26 wherein the first surface comprises a heat cured polymer selected from alkyd, polyester and acrylic.
30. A method comprising:
writing on a first sheet of a stack of a plurality of sheets, wherein each of the first
30 sheet and a second sheet comprises a first surface and a second surface, the first surface comprising a dry-erase coating and the second surface comprising a removable adhesive;

removing the first sheet from the stack;
adhering the first sheet to a substrate; and
writing on the second sheet.

- 5 31. The method of claim 30 wherein the step of writing on the first sheet precedes removing the first sheet from the stack.
32. The method of claim 30 comprising:
erasing substantially all of the writing from the first sheet;
10 removing the sheet from the substrate; and
adhering the first sheet to the stack.
33. The method of claim 30 wherein the first sheet is substantially transparent.
- 15 34. The method of claim 30 wherein the first surface exhibits a 60° gloss of less than 90 gloss units.
35. A kit comprising:
a first dry-erase surface comprising a dry-erase coating disposed on a substrate; and
20 instructions for affixing the first dry-erase surface to a second dry-erase surface.
36. The kit of claim 35 wherein an adhesive is disposed on the substrate.
37. The kit of claim 35 wherein the first dry-erase surface is flexible.
- 25 38. The kit of claim 35 wherein the first dry-erase surface is wound in a roll.
39. The kit of claim 35 wherein the first dry-erase surface exhibits a surface tension of greater than about 30 dynes/cm.
- 30 40. The kit of claim 35 wherein the dry-erase surface comprises a color.

- 41. The kit of claim 36 wherein a removable backing is in contact with the adhesive.
- 42. The kit of claim 41 wherein the removable backing comprises silicone-coated paper.